Starway

HERITAGE

PROFILE 250



GUIDE DE DÉMARRAGE

Réglementation

Cet appareil est parfaitement conçu. Il répond aux dispositions réglementaires actuelles : CE, ROHS, R&TTE

Recyclage

Appareil soumis à la DEEE (Collecte sélective). Contribuez à la protection de l'environnement en éliminant les matériaux d'emballage de ce produit via les filières de recyclage appropriées. Recyclez ce produit via une filière DEEE (déchets d'équipements électroniques). Ce produit doit être repris par votre revendeur ou doit être déposé dans un centre de collecte spécifique (déchetterie).

Garantie applicable en France

Le fabricant a apporté le plus grand soin à la conception et à la fabrication de votre produit pour qu'il vous apporte entière satisfaction. Néanmoins, s'il apparaissait que votre produit était défectueux, vous bénéficiez d'une garantie commerciale de 24 mois à compter de la date d'achat. Pour mettre en œuvre cette garantie, l'utilisateur doit présenter le produit au distributeur, accompagné du ticket de caisse ou la facture d'achat accompagnée du numéro de série.
Cette garantie, applicable en France, couvre tous les défauts du produit qui ne permettent pas une utilisation normale du produit. Elle ne couvre pas les défauts liés à un mauvais entretien, une utilisation inappropriée, une usure prévisible ; ou si les recommandations du fabricant n'ont pas été respectées.
La garantie ne couvre pas l'usure normale des pièces liée à l'utilisation du produit, tel que Batterie, Lampe, Roues, pièces d'usures, etc…
Eu égard au défaut et à la pièce concernée, le garant décidera alors de procéder à la réparation ou au remplacement de ladite pièce.
Le garant est : **CSI AUDIOVISUEL, 22, RUE ÉDOUARD BUFFARD - 77771 MONTEVRAIN, 01.48.63.22.11.**

La durée de fourniture de pièces détachées est de deux ans.

La garantie commerciale prévue ci-dessus ne limite aucunement le droit de l'acheteur d'agir en garantie des vices cachés ou de non-conformité, tel que prévu aux codes civil et de la consommation Française.

Consignes de sécurité

VEUILLEZ LIRE ATTENTIVEMENT ET CONSERVEZ CE MANUEL

Toute personne impliquée dans l'installation, l'utilisation et la maintenance de cet appareil doit être qualifiée et suivre les instructions comprises dans ce manuel.

Soyez prudent risques de chocs électriques !

Avant la mise en fonction, soyez certain que le produit n'ait pas subi de dommage durant le transport. Dans le cas contraire, contactez votre revendeur.
Afin de maintenir l'appareil en parfaites conditions, l'utilisateur doit suivre les instructions de sécurité et d'utilisation décrites dans ce présent document.
Notez que les dysfonctionnements liés à la modification de l'appareil ne sont pas couverts par la garantie.
Cet appareil ne contient aucune partie remplaçable par l'utilisateur, pour toute intervention contactez votre revendeur.



Soyez prudent risque photo-biologique !

Attention !! Système d'éclairage professionnel ne pas regarder le flux lumineux dans l'axe.



Risque d'incendie maintenir une distance minimale de 1 m entre le faisceau et une surface inflammable.

IMPORTANT :

Cet appareil doit être utilisé en intérieur avec une température ambiante inférieure à 40°.
Fixer le projecteur d'une façon stable.
Ne pas faire cheminer le câble d'alimentation avec les autres câbles.
Manipuler le câble d'alimentation avec les précautions d'usage.
Ne pas insérer d'objets dans les aérations.
Ne pas démonter ou modifier l'appareil. Risque d'électrocution !
Ne pas connecter cet appareil à un bloc de puissance.
Ne pas mettre En / Hors fonction de manière répétée.
Cet appareil doit être relié à la terre
N'utiliser cet appareil qu'après vous être familiarisé avec ses commandes et fonctions.
Eviter tout contact avec les flammes, éloignez l'appareil des surfaces inflammables.
Laisser toujours un espace suffisant autour de l'appareil pour permettre sa convection.
Déconnecter l'appareil du secteur, lorsqu'il n'est pas utilisé ou avant de le nettoyer.
Toujours débrancher l'alimentation en tenant la prise secteur et non le câble.
Vérifier que le cordon d'alimentation ne soit ni pincé ni endommagé, (prises et câbles)
Si l'appareil est tombé ou à reçu un choc, déconnecter le immédiatement du secteur et contacter un technicien qualifié pour le vérifier.
Si l'appareil a été soumis à d'importantes fluctuations de température, ne le mettez pas en fonction immédiatement, la condensation pourrait l'endommager en créant un CC (court-circuit).
Si l'appareil ne fonctionne pas correctement, mettez-le hors fonction immédiatement. Emballer-le, (de préférence dans son emballage d'origine).
Ce produit doit être utilisé exclusivement par un adulte en bonne santé.
Il doit être installé hors de portée des enfants.
Ne jamais utiliser le produit sans surveillance.
Ne pas utiliser l'appareil dans des zones ATEX ou et à proximité de d'hydrocarbure ou de produit inflammable.
Cet appareil doit être utilisé conformément à ce manuel, pour éviter tous dysfonctionnement

Nettoyage

Penser à nettoyer régulièrement l'optique avec un chiffon micro-pore.
L'usage d'air comprimé permet de nettoyer le boitier.

Le projecteur doit être sécurisé par une élingue de sécurité

Be green with Starway !*

Starway prend soin de notre belle planète et adopte l'éco-attitude !
Retrouvez les manuels en ligne et bien plus encore en flashant
le QR code apposé sur les produits !

Conçu pour les applications où la précision du faisceau et la discrétion d'intégration sont primordiales, **HERITAGE Profile 250** s'impose comme un outil de choix pour les environnements scéniques et architecturaux exigeants.
Compact et précis, il offre une qualité de lumière remarquable, parfaitement adaptée aux mises en scène soignées et aux éclairages de détail.
Son module **Spectral Core™** associé à la technologie **Pikr Core™** délivre une restitution colorimétrique riche, subtile et homogène. Avec un IRC > 97, **HERITAGE Profile 250** garantit un rendu exceptionnel des couleurs, des matières et des carnations, tout en assurant des blancs stables, constants et parfaitement reproductibles d'un projecteur à l'autre. Pour les applications les plus avancées, le pilotage en mode X,Y dans l'espace colorimétrique CIE 1931 permet un contrôle précis et normé de la couleur.
Le zoom manuel de 21° à 50° offre une grande souplesse d'utilisation, permettant d'adapter rapidement le faisceau à la distance, au cadrage et à la surface à éclairer.
Les couteaux de cadrage assurent une découpe nette et rigoureuse, idéale pour limiter les débordements lumineux, structurer l'espace et mettre en valeur un élément scénographique ou architectural avec précision.
Avec un flux lumineux pouvant atteindre 5 497 lumens, **HERITAGE Profile 250** se positionne comme une solution premium pour le théâtre, la télévision, les événements corporate et la muséographie, partout où la qualité de lumière et la maîtrise du faisceau font la différence.

SPÉCIFICATIONS TECHNIQUES :

- Source : SPECTRAL CORE™ - RGBALC - PikR Core™
- Optiques : 21 - 50°
- Flux Max : 5 497 lm
- DMX/RDM : 1/2/3CCT/14HSI /17RGBALC/23RGBALC/17CMY/19RGBW/15XY
- Mode : Auto, Statique, DMX
- XLR 5 Pins In/Out - PowerCon® In/Out
- Alimentation : AC100~240V - 50/60Hz
- Refroidissement - 3 Modes ventilations forcée
- Consommation max : 300W (@240V)
- Dimensions LxPxH : 471 x 290 x 423 mm
- Poids : 7.1 Kg

* Etre vert avec Starway !

Mode									Valeur	Fonction
1CH Dimmer	2CH Dimmer 16b	3CH Dimmer + CCT	14CH HSI	17CH RGBALC 8b	23CH RGBALC 16b	17CH CMY 16b	19CH RGBW 16b	15CH XY 16b		
1	1	1	1	1	1	1	1	1	000-255	Dimmer
	2	2	2	2	2	2	2	2	000-255	Dimmer fine
									000-009	Shutter fermé
									010-019	Shutter ouvert
									020-068	Strobe lent à rapide
			3	3	3	3	3	3	069-079	Shutter Ouvert
									080-128	Effet pulse en séquence
									129-139	Shutter Ouvert
									140-188	Strobe aléatoire lent à rapide
									189-255	Shutter Ouvert
			4	4	4	4	4	4	N/A	Réservé
				5	5		5		000-255	Rouge
					6		6		000-255	Rouge fine
				6	7		7		000-255	Vert
					8		8		000-255	Vert fine
				7	9		9		000-255	Bleu
					10		10		000-255	Bleu fine
				8	11				000-255	Ambre
					12				000-255	Ambre Fine
				9	13				000-255	Lime
					14				000-255	Lime Fine
				10	15				000-255	Cyan
					16				000-255	Cyan Fine
							11		000-255	Blanc (virtuel)
							12		000-255	Blanc fine
			5						000-255	Hue 0-360°
			6						000-255	Hue fine
			7						000-255	Saturation
						5			000-255	Cyan
						6			000-255	Cyan fine
						7			000-255	Magenta
						8			000-255	Magenta fine
						9			000-255	Jaune
						10			000-255	Jaune fine
								5	000-255	Coordonnées X CIE 1931 (0 > 0.8)
								6	000-255	X fine
								7	000-255	Coordonnées Y CIE 1931 (0 > 0.8)
								8	000-255	Y fine
		3	8	11	17	11	13	9	000-255	CCT 1800K à 10000K linéaire
									Tint : +/- Vert	
									000	Idle (DUVO)
			9	12	18	12	14	10	001-127	+ Magenta
									128	Idle (DUVO)
									129-255	+ Green
			10	13	19	13	15	11	000-255	Crossfade COLOR MIX / CCT WHITE
									000-255	Roued e couleurs virtuelle
									000-001	Idle
			11	14	20	14	16	12	002-250	Sélecteur de gélatines virtuelles
									251-253	Rotation CW
									254-255	Rotation CCW
			12	15	21	15	17	13	000-255	Virtual Colour Fade / Speed from fast to slow
									Modes du Dimmer	
									000-020	Selon Menu du projecteur
									021-040	DimO
			13	16	22	16	18	14	041-060	Dim1
									061-080	Dim2
									081-100	Dim3
									101-255	Dim4
									Contrôle	
									000-004	Idle
									005-044	Reservé
									045-049	Fan Quiet (Hold 3s)
									050-054	Fan Auto (Hold 3s)
									055-059	Fan High (Hold 3s)
									060-064	Linear Dimmer Curve (3s)
									065-069	Square Dimmer Curve (3s)
			14	17	23	17	19	15	070-074	Inv-Square Dimmer Curve (3s)
									075-079	S - Dimmer Curve (3s)
									080-084	Fast Dimmer OFF (3s)
									085-089	Fast Dimmer ON (3s)
									090-159	Led Freq. 900 Hz to 25kHz (3s)
									160-169	Réservé
									170-174	Activation du Redshift (effet tungstène sur le canal CCT et en mode Gel)
									175-179	Desactivation du Redshift (effet tungstène sur le canal CCT et en mode Gel)
									180-255	Réservé

Retrouvez le manuel en flashant le QR code apposé sur les produits ou en cliquant sur le lien ci dessous :

https://tech.starway.eu/225570_P250/225570_P250_ML.pdf

STARWAY

22, rue Édouard Buffard - MONTEVRAIN 77144

France

Tél. : +33 (0)820 230 007

starway.eu

Starway

HERITAGE

PROFILE 250



QUICK START

WARNING! Before carrying out any operations with the unit, carefully read this instruction manual and keep it with cure for future reference. It contains important about the installation, usage and maintenance of the unit.

SAFETY

General Instruction

- **The products referred to in this manual conform to the European Community Directives and are there-fore marked with CE:.**
- **The unit is supplied with hazardous network voltage (240V~). Leave servicing to skilled personnel only. Never make any modifications on the unit not described in this instruction manual, otherwise you will risk an electric shock.**
- **Connection must be made to a power supply system fitted with efficient earthing (Class I appliance ac-cording to standard EN 60598-1). It is, moreover, recommended to protect the supply lines of the units from indirect contact and/or shorting to earth by using appropriately sized residual current devices.**
- **The connection to the main network of electric distribution must be carried out by a qualified electrical installer. Check that the main frequency and voltage correspond to those for which the unit is designed as given on the electrical data label.**
- **Never use the fixture under the following conditions:**
  - in places wet;
  - in places subject to vibrations or bumps;
  - in places with an ambient temperature of over 40° C.
- **Make certain that no inflammable liquids, water or metal objects enter the fixture.**
- **Do not dismantle or modify the fixture.**
- **All work must always be carried out by qualified technical personnel. Contact the nearest sales point for an inspection or contact the manufacturer directly.**
- **If the unit is to be put out of operation definitively, take it to a local recycling plant for a disposal which is not harmful to the environment.**

Warnings and installation precautions

- Never let the power cord come into contact with other cables! Handle the power cord and all connections with the mains with particular caution!
- Never modify, bend, mechanically strain, put pressure on, pull or heat up the power cord.
- Never strain the cable. There must always be sufficient cable going to the device. Otherwise, the cable will be damaged, which can cause serious damage.
- Never remove warning or informative labels from the unit.
- Never use anything to cover the ground contact.
- Never lift the device holding it by the projector-head, as the mechanics may be damaged
- Do not shake the device. Avoid brute force when installing or operating the device.
- Only operate the device after having checked if the housing is firmly closed and all screws are tightly fastened.
- Only operate the device after having familiarized with its functions.
- Avoid flames and do not put close to flammable liquids or gases.
- Always allow a free air space of at least 0.8 m around the unit for ventilation.
- Always disconnect power from the mains, when device is not used or before cleaning! Only handle the power cord holding it by the plug. Never pull out the plug by tugging the power cord.
- Make sure that the device is not exposed to extreme heat or dust.
- Make sure that the available voltage is not higher than stated on the rear panel.
- Make sure that the power cord is never crimped or damaged. Check the device and the power cord from time to time.
- Make sure that the core diameter of extension cords and power cords is sufficient for the required power consumption of the device.
- Always hold the device by the transport handles.
- Never place any material over the LEDs or lens.
- Never look directly into the light source.
- Never leave any cables lying around.
- Never use the device during thunderstorms, unplug the device immediately.
- Never leave various parts of the packaging (plastic bags, polystyrene foam, nails, etc within children's reach, as they potential sources of danger.
- Do not insert objects into air vents.
- Do not open the device and do not modify the device.
- Do not connect this device to a dimmer pack.
- Do not switch the device on and off in short intervals, as this will reduce the device's life.
- Do not touch the device's housing bare-handed during its operation (housing becomes very hot). Allow the device to cool for at least 5 minutes before handling.
- If the lens or LEDs are obviously damaged, they need to be replaced to prevent their functions from being impaired, due to cracks or deep scratches.
- If the external cable is damaged, it has to be replaced by a qualified technician.
- If device was dropped or struck, disconnect mains power supply immediately. Have a qualified engineer inspect for safety before operating.
- If the device has been exposed to drastic temperature fluctuation (e.g. after transportation), do not switch it on immediately. The arising condensation water might damage your device. Leave the device switched off until it has reached room temperature.
- If your device fails to work properly, discontinue the use immediately. Pack the unit securely (preferably in the original packing material), and return it to your dealer for service.
- For adult use only. The device must be installed beyond the reach of children. Never leave the unit running unattended.
- Never attempt to bypass the thermostatic switch or fuses.
- For replacement use fuses of same type and rating only.
- This device is heavy. When handling, use a two-person lift to prevent injury.
- The user is responsible for correct positioning and operating of the device. The manufacturer will not accept liability for damages caused by the misuse or incorrect installation of this device.
- This device falls under protection class I. Therefore it is essential to connect the yellow/green conductor to earth.
- Repairs, servicing and electric connection must be carried out by a qualified technician.

Rigging

This device is heavy. When handling, use a two-person lift to prevent injury.

Please follow the European and national guidelines concerning rigging, trussing and all other safety issues.

Be green with Starway !

Starway takes care of our beautiful planet and adopts the eco-attitude!
Find manuals online and more by flashing the QR code on the products!

Designed for applications where beam precision and unobtrusive integration are paramount, **HERITAGE Profile 250** is the tool of choice for demanding scenic and architectural environments. Compact and precise, it offers remarkable light quality, perfectly suited to meticulous staging and detail lighting.
Its **Spectral Core™** module combined with **Pikr Core™** technology delivers rich, subtle and homogeneous color reproduction. With a CRI > 97, **HERITAGE Profile 250** guarantees exceptional rendering of colors, materials and skin tones, while ensuring stable, consistent whites that are perfectly reproducible from one projector to the next. For the most advanced applications, X,Y mode control in CIE 1931 color space enables precise, standardized color control.
The manual zoom from 21° to 50° offers great flexibility, enabling the beam to be quickly adapted to the distance, framing and surface to be illuminated. The framing knives ensure a clean, rigorous cut, ideal for limiting light spillover, structuring space and highlighting a scenographic or architectural element with precision.
With a luminous flux of up to 5497 lumens, **HERITAGE Profile 250** is positioned as a premium solution for theater, television, corporate events and museography, wherever light quality and beam control make the difference.

Technical specifications :

- Source : SPECTRAL CORE™ - RGBALC - PikR Core™
- Optics : 21° - 50°
- Max Flux : 5 497 lm
- DMX/RDM : 1/2/3CCT/14HSI /17RGBALC/23RGBALC/17CMY/19RGBW/15XY
- Mode : Auto, Static, DMX
- XLR 5 Pins In/Out - PowerCon® In/Out
- Power : AC100~240V - 50/60Hz
- Cooling : 3 Mode - Forced ventilation
- Consumption max : 300W (@240V)
- Dimensions LxPxH : 471 x 290 x 423 mm
- Weight : 7.1 Kg

Mode									Value	Function
1CH Dimmer	2CH Dimmer 16B	3CH Dimmer + CCT	14CH HSI	17CH RGBALC 8b	23CH RGBALC 16b	17CH CMY 16b	19CH RGBW 8b	15CH XY 16b		
1	1	1	1	1	1	1	1	1	000-255	Dimmer
	2	2	2	2	2	2	2	2	000-255	Dimmer fine
			3	3	3	3	3	3	000-009	Shutter closed
									010-019	Shutter open
									020-068	Strobe effect slow to fast
									069-079	No function (shutter open)
									080-128	Pulse-effect in sequences
									129-139	No function (shutter open)
									140-188	Random strobe effect slow to fast
									189-255	No function (shutter open)
			4	4	4	4	4	4	N/A	Reserved
				5	5		5		000-255	Red
					6		6		000-255	Red Fine
				6	7		7		000-255	Green
					8		8		000-255	Green Fine
				7	9		9		000-255	Blue
					10		10		000-255	Blue Fine
				8	11				000-255	Amber
					12				000-255	Amber Fine
				9	13				000-255	Lime
					14				000-255	Lime Fine
				10	15				000-255	Cyan
					16				000-255	Cyan Fine
							11		000-255	White (virtual)
							12		000-255	White Fine
			5						000-255	Hue 0-360°
			6						000-255	Hue fine
			7						000-255	Saturation
						5			000-255	Cyan
						6			000-255	Cyan fine
						7			000-255	Magenta
						8			000-255	Magenta fine
						9			000-255	Yellow
						10			000-255	Yellow fine
								5	000-255	X CIE 1931 coordinate (0 > 0.8)
								6	000-255	X fine
								7	000-255	Y CIE 1931 coordinate (0 > 0.8)
								8	000-255	Y fine
		3	8	11	17	11	13	9	000-255	CCT white linear from 1800K to 10 000K
									Tint : +/- green	
			9	12	18	12	14	10	000	Idle (DUV 0)
									001-127	+ Magenta
									128	Idle (DUV 0)
									129-255	+ Green
			10	13	19	13	15	11	000-255	Crossfade between COLOR MIX and CCT WHITE channel
			11	14	20	14	16	12	000-255	Virtual wheel color
									000-001	Idle
									002-250	Virtual Gel wheel
									251-253	Color Wheel rotation CW
									254-255	Color rotation backward CCW
			12	15	21	15	17	13	000-255	Virtual Colour Fade / Speed from fast to slow
									Dim Modes:	
			13	16	22	16	18	14	000-020	Default unit setting
									021-040	Dim0
									041-060	Dim1
									061-080	Dim2
									081-100	Dim3
									101-255	Dim4
			14	17	23	17	19	15	Control	
									000-004	Idle
									005-044	Reserved
									045-049	Fan Quiet(Hold 3s)
									050-054	Fan Auto (Hold 3s)
									055-059	Fan High (Hold 3s)
									060-064	Linear Dimmer Curve (hold 3s)
									065-069	Square Dimmer Curve (hold 3s)
									070-074	Inv-Square Dimmer Curve (hold 3s)
									075-079	S - Dimmer Curve (hold 3s)
									080-084	Fast Dim disable (hold 3s)
									085-089	Fast Dim enable (hold 3s)
									090-159	Led Freq. 900 Hz to 25 kHz (hold 3s)
									160-169	Reserved
									170-174	Enable Redshift (tungsten effect in CCT channel and gel mode) (3s)
									175-179	Disable Redshift (tungsten effect in CCT channel and gel mode) (3s)
									180-255	Reserved

Find the manual available by flashing the QR code affixed to the products or by clicking on the link below:

https://tech.starway.eu/225570_P250/225570_P250_ML.pdf

Please note that the manuals are multi-language

STARWAY

22, RUE ÉDOUARD BUFFARD - MONTEVRAIN 77144

France

Tél. : +33 (0)820 230 007

starway.eu